



T200 Series

Common Specifications

Farming for the Future

Gyral Implements Pty Ltd
 ABN 70 009 682 884
 285 McDougall Street
 PO Box 6046
 Toowoomba QLD 4350
 Telephone: 07 4634 3388

Max Working Depth 150mm
Max Tyne Jump Approx 280mm
Road Clearance Approx 350mm
Underframe Clearance 470mm

(Standard Point on 65 Sq. Beam)

Direct Drill Options (a) Lucerene Point
 (b) Spear Point & Adaptor Assembly

Cultivation 6 beam
Tyne Options 25mm Sq – 145lb BreakOut
 30mm Rd. Solid – 180lb BreakOut
Tyne Material High Grade Spring Steel (30mm Shot Peened)

	T220	T225	T226
Tyne Spacing	115mm (4 ¹ / ₂ "	127mm (5")	150mm (5 ⁷ / ₈ "
Plant Row Spacing	230mm (9")	254mm (10")	150mm (5 ⁷ / ₈ " or 300mm
POINTS			
Standard Bolt-On	150mm (6")	180mm (7")	180mm (7")
Optional Knock-On	165mm (6 ¹ / ₂ "	190mm (7 ¹ / ₂ "	190mm (7 ¹ / ₂ "

T220 Series Tilter Specifications

Single Fold 3-Section Models								
Machine Size	No of Heads	Seeder Outlets	Folded Width	Centre Frame			Wing	
	Row Spacings			Width	Tyres	Wheel Centres	Width	Tyres
	230mm	230mm						
6.44m (21'2")	2	28	5.02m (16'6")	3.68m (12'1")	9.00 x 16" (10 ply)	2.80m (9'2")	1.38m (4'6")	7.50 x 16" (6 ply)
7.36m (24'2")	2	32	5.02m (16'6")	3.68m (12'1")	9.00 x 16" (10 ply)	2.80m (9'2")	1.84m (6'0")	7.50 x 16" (6 ply)
8.28m (27'2")	3	36	5.02m (16'6")	3.68m (12'1")	9.00 x 16" (10 ply)	2.80m (9'2")	230m (7'6")	7.50 x 16" (6 ply)
9.66m (31'9")	3	42	5.02m (16'6")	3.68m (12'1")	9.00 x 16" (10 ply)	2.80m (9'2")	2.99m (9'10")	7.50 x 16" (6 ply)
11.04m (36'3")	3	48	6.40m (21'0")	5.06m (16'7")	12.00 x 16" (12 ply)	4.26m (14'0")	2.99m (9'10")	9.00 x 16" (10 ply)
12.42m (40'9")	3	54	6.40m (21'0")	5.06m (16'7")	12.00 x 16" (12 ply)	4.26m (14'0")	3.68m (12'1")	9.00 x 16" (10 ply)

Single Fold 5-Section Models										
Machine Size	No of Heads	Seeder Outlets	Folded Width	Centre Frame			Inside Wing		Outside Wing	
	Row Spacings			Width	Tyres	Wheel Centres	Width	Tyres	Width	Tyres
	230mm	230mm								
12.42m (40'9")	3	54	5.02m (16'6")	3.68m (12'1")	12.0 x 16" (12 ply)	2.80m (9'11")	2.76m (9'1")	9.00 x 16" (10 ply)	1.61m (5'3")	7.50 x 16" (6 ply)
13.80m (45'4")	4	60	6.40m (21'0")	5.06m (16'7")	12.0 x 16" (12 ply)	4.26m (14'0")	2.76m (9'1")	9.00 x 16" (10 ply)	1.61m (5'3")	7.50 x 16" (6 ply)
14.72m (48'4")	4	64	6.40m (21'0")	5.06m (16'7")	12.0 x 16" (12 ply)	4.26m (14'0")	2.76m (9'1")	9.00 x 16" (10 ply)	2.07m (6'10")	7.50 x 16" (6 ply)



Gyral Implements Pty Ltd

Farming for the Future

T225 Series Tillers Specifications

Single Fold 3-Section models Row Spacing 254mm

Machine Size	No of Seeder Outlets		Folded Width	Centre Frame		Inside Wing		Outside Wing	
	Row Spacings			Width	Tyres	Wheel Centres	Width	Tyres	
	254mm	254mm							
7.112m (23'4")	2	28	5.44m (17'9")	4.064m (13'4")	9.00 x 16" (10 ply)	3.170m (10'5")	1.524m (5'0")	7.50 x 16" (6 ply)	
8.128m (26'8")	2	32	5.44m (17'9")	4.064m (13'4")	9.00 x 16" (10 ply)	3.170m (10'5")	2.032m (6'8")	7.50 x 16" (6 ply)	
9.144m (30'0")	3	36	5.44m (17'9")	4.064m (13'4")	9.00 x 16" (10 ply)	3.170m (10'5")	2.540m (8'4")	7.50 x 16" (6 ply)	
10.668m (35'0")	3	42	5.44m (17'9")	4.064m (13'4")	12.0 x 16" (12 ply)	3.170m (10'5")	3.302m (10'10")	9.00 x 16" (10 ply)	
12.192m (40'0")	3	48	6.97m (22'9")	5.588m (18'4")	12.0 x 16" (12 ply)	4.700m (15'5")	3.302m (10'10")	9.00 x 16" (10 ply)	

Double Fold 5-Section Models

Machine Size	No of Seeder Outlets		Folded Width	Centre Frame		Inside Wing		Outside Wing		
	Row Spacings			Width	Tyres	Wheel Centres	Width	Tyres	Width	Tyres
	254mm	254mm								
12.192m (40'0")	3	48	5.44m (17'9")	4.064m (13'4")	12.0 x 16" (12 ply)	3.170m (10'5")	2.286m (7'6")	9.00 x 16" (10 ply)	1.778m (5'10")	7.50 x 16" (6 ply)
14.224m (46'8")	4	56	5.44m (17'9")	4.064m (13'4")	12.0 x 16" (12 ply)	3.170m (10'5")	3.048m (10'0")	9.00 x 16" (10 ply)	2.032m (6'8")	7.50 x 16" (6 ply)
15.240m (50'0")	4	60	6.97m (22'9")	5.588m (18'4")	12.0 x 16" (12 ply)	4.700m (15'5")	3.048m (10'0")	9.00 x 16" (10 ply)	1.778m (5'10")	7.50 x 16" (6 ply)

T226 Series Tillers Specifications

Single Fold 3-Section Models

Machine Size	No of Heads		Seeder Outlets		Folded Width	Centre Frame			Wing	
	Row Spacings		150mm	300mm		Width	Tyres	Wheel Centres	Width	Tyres
	150mm	300mm								
6.75m (22'2")	3	2	45	22	4.96m (16'3")	3.60m (11'10")	9.00 x 16" (10 ply)	2.37m (7'9")	1.50m (4'11")	7.50 x 16" (6 ply)
7.65m (25'1")	3	2	51	24	4.96m (16'3")	3.60m (11'10")	9.00 x 16" (10 ply)	2.37m (7'9")	1.95m (6'5")	7.50 x 16" (6 ply)
9.00m (29'6")	3	3	60	30	4.96m (16'3")	3.60m (11'10")	9.00 x 16" (10 ply)	2.37m (7'9")	2.70m (8'10")	7.50 x 16" (6 ply)
10.20m (33'6")	4	3	68	34	4.96m (16'3")	3.60m (11'10")	9.00 x 16" (10 ply)	2.37m (7'9")	3.30m (10'10")	7.50 x 16" (6 ply)
10.80m (35'5")	4	3	72	36	4.96m (16'3")	3.60m (11'10")	12.00 x 16" (12 ply)	2.37m (7'9")	3.60m (11'10")	9.00 x 16" (10 ply)
10.80m (35'5")	4	3	72	36	6.16m (20'2")	4.80m (15'9")	12.00 x 16" (12 ply)	3.57m (11'9")	3.00m (9'10")	9.00 x 16" (10 ply)
12.0m (39'4")	4	3	80	40	6.16m (20'2")	4.80m (15'9")	12.00 x 16" (12 ply)	3.57m (11'9")	3.60m (11'10")	9.00 x 16" (10 ply)

Single Fold 5-Section Models

Machine Size	No of Heads		Seeder Outlets		Folded Width	Centre Frame			Inside Wing		Outside Wing	
	Row Spacings		150mm	300mm		Width	Tyres	Wheel Centres	Width	Tyres	width	Tyres
	150mm	300mm										
12.0m (39'4")	4	3	80	4	4.96m (16'3")	3.60m (11'10")	12.0 x 16" (12 ply)	2.37m (8'10")	2.70m (8'10")	9.00 x 16" (10 ply)	1.50m (4'11")	7.50 x 16" (6 ply)
3.20m (43'4")	4	4	88	44	6.16m (20'2")	4.80m (15'9")	12.0 x 16" (12 ply)	3.57m (11'9")	2.70m (8'10")	9.00 x 16" (10 ply)	1.50m (4'11")	7.50 x 16" (6 ply)
14.40m (47'3")	5	4	96	48	6.16m (20'2")	4.80m (15'9")	12.0 x 16" (12 ply)	3.57m (11'9")	2.70m (8'10")	9.00 x 16" (10 ply)	2.10m (6'11")	7.50 x 16" (6 ply)